

## Aluminium- Rechteckrohre


EN 573-3, 755-1, -2, -9

In Herstellungslängen von  
ca. 6 m

EN AW-6060

Werkstoff-Nr. 3.3206

Al Mg Si 0,5 F 22



mm (A x B x S)	kg/m	mm (A x B x S)	kg/m	mm (A x B x S)	kg/m
20 x 10 x 1,5	0,230	50 x 30 x 2	0,830	100 x 30 x 3	2,000
20 x 10 x 2	0,300	50 x 30 x 3	1,200	100 x 40 x 3	2,170
20 x 15 x 2	0,350	50 x 40 x 2	1,000	100 x 40 x 4	2,940
25 x 15 x 2	0,395	50 x 40 x 2,5	1,150	100 x 50 x 2	1,580
25 x 20 x 2	0,440	50 x 40 x 3	1,300	100 x 50 x 3	2,330
30 x 10 x 1	0,210	50 x 40 x 4	1,800	100 x 50 x 4	3,070
30 x 10 x 1,50	0,320	60 x 20 x 2	0,822	100 x 50 x 5	4,000
30 x 15 x 2	0,440	60 x 20 x 4	1,644	100 x 60 x 3	2,950
30 x 20 x 2	0,496	60 x 25 x 2	0,880	100 x 60 x 4	3,290
30 x 20 x 3	0,800	60 x 25 x 3	1,300	100 x 80 x 3	3,000
30 x 25 x 2	0,580	60 x 30 x 2	0,929	120 x 20 x 2	1,470
35 x 15 x 2	0,520	60 x 30 x 3	1,430	120 x 30 x 2	1,600
35 x 20 x 2	0,580	60 x 40 x 2	1,080	120 x 30 x 3	2,500
35 x 25 x 1,5	0,480	60 x 40 x 2,5	1,320	120 x 40 x 4	3,370
35 x 25 x 2	0,605	60 x 40 x 3	1,550	120 x 60 x 4	3,720
40 x 10 x 2	0,520	60 x 40 x 4	1,990	120 x 80 x 3	3,300
40 x 15 x 2	0,550	60 x 50 x 3	1,690	150 x 18 x 2	1,900
40 x 20 x 1,5	0,500	70 x 20 x 2	0,960	150 x 40 x 4	3,950
40 x 20 x 2	0,602	70 x 25 x 2,5	1,220	150 x 50 x 4	4,150
40 x 20 x 2,5	0,745	70 x 30 x 3	1,600	160 x 40 x 4	4,100
40 x 20 x 3	0,880	80 x 20 x 2	1,080	160 x 60 x 4	4,500
40 x 20 x 4	1,080	80 x 30 x 2	1,166	160 x 80 x 3	5,000
40 x 25 x 2	0,660	80 x 30 x 3	1,690	160 x 80 x 4	5,100
40 x 30 x 2	0,713	80 x 40 x 2	1,300	170 x 70 x 4	5,100
40 x 30 x 3	1,100	80 x 40 x 2,5	1,586	180 x 40 x 4	5,100
40 x 30 x 4	1,360	80 x 40 x 3	1,840	180 x 50 x 4	4,800
50 x 15 x 2	0,660	80 x 40 x 4	2,419	200 x 40 x 3	4,450
50 x 20 x 2	0,715	80 x 50 x 3	2,057	200 x 50 x 4	5,500
50 x 20 x 3	1,040	80 x 50 x 4	2,640	200 x 100 x 4	6,220
50 x 20 x 4	1,340	80 x 60 x 3	2,300	200 x 100 x 5	8,100
50 x 25 x 2	0,820	80 x 60 x 4	2,100		

## Aluminium-Draht

in Ringen

EN AW-1050 A

Al 99,5

**weich in Ringen**

mm	kg/100m	mm	kg/100m
1	0,212	3	1,910
1,5	0,480	4	3,390
2	0,850	5	5,300
2,5	1,410		

EN AW-1050 a

Al 99,5

**1/2 hart in Ringen**

mm	kg/100m	mm	kg/100m
0,5	0,053	3	1,910
1	0,212	4	3,390
1,5	0,480	6	7,900
2	0,850	8	13,600

EN AW-1050 a

Al 99,5

**hart in Ringen**

mm	kg/100m	mm	kg/100m
1,0	0,220	4,0	3,390
2,0	0,850	6,0	7,6004
3,0	1,910		

EN AW-5754

Al Mg 3

**F 23 1/2 hart in Ringen**

mm	kg/100m
1,5	0,480
2,0	0,850